





VoIP Industrial telephone Type A24/VoIP With the proven casing of the weatherproof telephone A24 combined with newest IP-Network-Technology the A24/VoIP will be the new component for your communication system. The configuration is realized by a simple and clearly arranged web-interface. All hardware combinations of the A24 are also available for the A24/VoIP. The brightness of the optional available lighted keypad is adjustable. As known from our A24 you can also connect the headset WHA to the A24/VoIP.

VolP Industrial telephone

Type A24/VoIP



Technical data	
Storage temperature	-40°C - +70°C
Operating temperature	-20°C - +60°C
Relative humidity	max 95%
Casing enclosure	IP 66
Features	SIPaccording to RFC 3261, Ethernet 10/100 MbitTagged VLAN according to IEE 802.1Q POE according to IEE 802.3af phantom power included Power consumption about 3W Firmwareupdate via TFTP-Server and web-Interface
Tone signaling volume	60 dB - 97 dB in 1m distance
Functions	depending on number of keys 4-6 functions, redialing, mute, receiver amplification 4x + 3dB, Headset, 4 direct dialing buttons
Codes	G711, GSM, A-law, μ-law, Speex
Cable gland	M16, Ø 5-10mm Dummy plugs: I x M12*, I x M16 Handset: M12Flex, Ø 3-6,5mm
Material	Casing: Polyamide Locking screws: V4A (1.4571)

Model	Order no
with spiral handset cord	01.61000
with spiral handset cord + I special key	01.61001
with spiral handset cord + 2 special keys	01.61002
with stainless steel handset cord	01.62000
with stainless steel handset cord + I special key	01.62001
with stainless steel handset cord + 2 special keys	01.62002
with lighted keypad + spiral handset cord	01.63000
with lighted keypad + spiral handset cord + I special key	01.63001
with lighted keypad + spiral handset cord + 2 special keys	01.63002
with lighted keypad + stainless steel handset cord	01.64000
with lighted keypad + stainless steel handset cord + 1 special key	01.64001
with lighted keypad + stainless steel handset cord + 2 special keys	01.64002

Dimensioned drawing ca.154

Dimension:

221 (height) x 154 (width) x 105 (depth) mm

128-134

Distance between holes for mounting:

128-134mm

Weight:

approx. 1250g



